

## Composites

### Datasheet

# Finishmat® D88



#### Lantor Finishmat® D88

- Lofty, needle punched polyester veil
- Compatible with thermoset resins
- Easy to process due to high tensile strength
- To be used in chemical barrier layers
- Instant and good resin wet-out
- Logo print possibility on request

#### Applications Lantor Finishmat® D88

- Industrial applications: tanks, pipes, containers, profiles and rods
- Very suitable for filament winding, pultrusion processing and RTM light

Properties		D88
Thickness*	mm	0,65
Roll length	m	1050
Roll width	m	0,95
Dry weight	g/m <sup>2</sup>	80
Resin uptake*	kg/m <sup>2</sup>	0,40
Binder		Needle punched
Tensile strength	N/cm	17
Elongation	%	>50
Fibre	type	Polyester

\* Depending on process pressure

The information contained in this document has been compiled in good faith by Lantor BV, but nevertheless no representation or warranty is given as to the accuracy or completeness of the (technical) information provided herein. Lantor BV can not be held liable of any damages arising from any (printing) errors or omissions in this information. Lantor BV reserves the right to make changes with respect to the information provided at any time without further notice.

#### Information

Verlaat 22 - 3901 RG  
Veenendaal - The Netherlands  
t +31 (0)318 537 111  
e composites@lantor.com

enabling performance

[www.lantorcomposites.com](http://www.lantorcomposites.com)

